

PID Code/Condition: 186-1508 / 186AB6

Description: Mack AL461 Rear Air Suspension

Models: ALL

Date: October 14, 2016

MACK AL461 AIR SUSPENSION

- Superior Driver Comfort
- Exceptional Handling
- On and off-road applications

The 46,000 pound capacity AL461 air suspension is built to operate under off-highway conditions up to 25 percent of the time and is approved for use with one or more lift axles.

Sales Engineering

Mack Trucks, Inc. Allentown, PA 18103 United States

Phone: 800 868 6225 Fax: 610 351 8791

MackTrucks.com



The information in this document was accurate as of the date of release and pertains to the current version of Mack's Sales Tool. Mack Trucks, Inc. reserves the right to make changes in specifications, equipment or design, or to discontinue models or options without notice.

SALES • ENGINEERING • DEPARTMENT



| Suspension Model | Suspension Capacity (lbs.) | GCW Approval (lbs.)¹ | GVW Approval (lbs.)' | Service: On/Off- Highway | Tractor | Truck | Suspension Weight (lbs.)² | Site Rating (lbs.)³ |
|---------------------|----------------------------------|----------------------------|----------------------------|--------------------------------|------------------|-------|---------------------------------|---------------------------|
| AL461 | 46,000 | 150,000 | 76,000 | On/Off | Yes ⁴ | Yes 6 | 937 | 50,000 |

Approved Applications

| | AL461 |
|----------------------------------|-------|
| General Freight (Van or Flatbed) | X |
| Refrigerated (No Swinging Meat) | Х |
| Refrigerated (Swinging Meat) | X |
| Car Carrier | X |
| Chip Hauler | X |
| Concrete Pumper | Х |
| Block Hauler | Х |
| Wrecker | X |
| Dump | Х |
| Logger | Х |
| Oil Field | |
| Refuse (Transfer and Recyler) | Х |
| Heavy Equipment Hauler | Х |
| Mixer | Χ7 |
| Beverage | X |
| Doubles / Triples | X |
| Fire / Rescue | X |

- Contact Hendrickson or original equipment manufacturer for applications that may exceed GVW / GCW approval ratings.
 Installed weight includes complete suspension, torque rods, axle and frame brackets and all hardware.
- Operators using vehicles equipped with liftable push or tag axles must not exceed published ratings.
 Not approved with trailer belly lift axles.
- 5. No add-on lift axles.
- 6. One more lift axles. Maximum 50,000-lb. load on suspension for site travel.
- 7. Not approved for straight truck applications.

The information in this document was accurate as of the date of release and pertains to the current version of Mack's Sales Tool. Mack Trucks, Inc. reserves the right to make changes in specifications, equipment or design, or to discontinue models or options without notice.