

FACT SHEET

ROOF HATCH



Roof hatch and sky window.

All cabs (excluding low day cabs and low sleeper cabs) are equipped with an escape possibility via the roof, either a fixed sky window or a roof hatch. The sky window is made of tinted glass, and the roof hatch is offered in steel or tinted glass. For the glass sky window and the roof hatch in glass, a sun blind is standard.

A steel roof hatch is more suitable for construction and other rough conditions, designed to cope with pebbles and being hit by minor branches. It reduces heat radiation in sunny, hot conditions and is isolated to reduce noise.

The roof hatch can be opened for ventilation with a manual handle. The opening length of the roof hatch is 500 mm and the width is 700 mm (all sales variants excluding URH). For the roof hatch, an additional mosquito net is standard.



Emergency handle for Volvo FM/FH laminated glass sky window and roof hatch.



DRIVER APPEAL

- Starts air circulation and provides quick ventilation (excluding RH-EE).
- Lets daylight into the cab even when the hatch is shut (excluding RH-ER).
- Stepless electrical operation facilitates opening and shutting (only RH-ETR/RH-ER).

Sales variants

RH-EE	Roof skylight/emergency exit, tinted glass (not a hatch)
RH-ETR	Roof hatch, electrically operated, tinted glass, rear opening 50 mm
RH-ER	Roof hatch, electrically operated, steel, with emergency exit handle
RH-MTR	Roof hatch, manually operated, tinted glass, rear opening 50 mm.
URH	Without roof hatch.

FACT SHEET

ROOF HATCH



RH-MTR/RH-ETR.



RH-MTR.



RH-ER



RH-ETR.