


MODEL RANGE

FE 64 Rigid Rear Leaf B-ride FE 64 R B



Chassis Dimensions [mm]

WB Wheelbase	3495	3845	4195	4495	4995	5495
A Overall Chassis Length	7610	8710	9710	9360	10160	11010
D Center of rear axle to front of body	2856	3206	3556	3856	4356	4856
N Rear Overhang (Min.)	830	830	1240	830	830	830
N Rear Overhang (Max.)	1325	2075	2725	2075	2375	2725
T Theoretical Wheelbase	4180	4530	4880	5180	5680	6180
Y Center of Gravity for Payload (Min.)	-63	-8	46	79	149	217
Y Center of Gravity for Payload (Max.)	-63	-8	46	79	149	217
W Body Length (Min.)	5838	6427	7019	7554	8414	9249
W Body Length (Max.)	5838	6427	7019	7554	8414	9249

Chassis Weights [kg]

Front Axle	4045	4045	4050	4100	4125	4160
Rear Bogie	3535	3615	3705	3650	3705	3785
Kerb Weight	7580	7660	7755	7750	7830	7945
Payload (including body, driver, fuel, etc.)	20520	20440	20345	20350	20270	20155

Turning Diameter [mm]

Turning Circle Diameter Kerb to Kerb	14900	16000	17100	18000	19500	21100
Turning Circle Diameter Wall to Wall	16300	17400	18500	19400	21000	22500

Plated Weights [kg]

	Design
Gross Vehicle Weight	28100
Gross Combination Weight	32000
Front Axle	7100
Rear Bogie	21000

Important Notes

Chassis Dimensions

Front Axle to Back of Cab: +375 mm for CAB-SLP, +204 mm for CAB-SSLP.
D-measure includes a front clearance of 74 mm and for rigid trucks also a subframe of 120 mm.
Height can vary ± 20 mm for leaf and ± 10 mm for air suspension.
All dimensions are for unladen chassis and any tag axles down.

Weight and dimensions are based upon the following tyres:

Front Axle Tyres: 295/80R22.5
Drive Axle Tyres: 295/80R22.5

Chassis weight includes oil, water, AdBlue, 0 litres fuel and without driver. Kerb weight can vary $\pm 3\%$.

Turning diameters are theoretically calculated.

Legal weights can differ from country to country.

For more detailed weight information, including optional equipment weights, ask your Volvo sales contact to enter your specification into the Volvo Weight Information system (WIS).

Do NOT use this drawing for bodybuilding. Refer to Volvo Bodybuilder Instructions and chassis assembly drawing FE64RB.

MODEL RANGE

FE 64 Rigid Rear Leaf B-ride FE 64 R B

Transport operation

- **TGW-4G**
- **RC-ROUGH** Rough road conditions: frequent driving on poorly maintained surfaced roads, hard-packed sand or gravel, or other surfaces of good or bad quality.
- **TIPP-PRE** Tipper vehicle preparation
- **UNIFORM** Basic platform vehicle

Core components

- **CHH-HIGH** Chassis height high - approx. 1000 mm above ground level
- **RADD-BR** Rear leaf suspension - two axles, both driving (B-ride)
- **FE-DAY2** FE Day cab new
- **FE-SLP2** FE Sleeper cab
- **FE-SSLP2** FE Comfort cab
- **EU6SCR** Euro 6 with SCR, particulate filter and EGR, Turbo-S
- **D8K280** Diesel engine, Euro 6, 7.7 litres, 280 hp/206 kW, 1050 Nm
- **D8K320** Diesel engine, Euro 6, 7.7 litres, 320 hp/235 kW, 1200 Nm
- **D8K350** Diesel engine, Euro 6, 7.7 litres, 350 hp/258 kW, 1400 Nm
- **EBR-CEB** Engine compression and exhaust brake
- **EBR-EPG** Engine brake with exhaust pressure governor
- **AL306** Automatic 6-speed gearbox, 1695 Nm
- **AT2412F** I-Shift automated 12-speed gearbox, 2400 Nm
- **ZTO1109** Manual 9-speed gearbox, 1200 Nm
- **RTH2180C**
- **RTS2370A** Rear single reduction tandem axle - bogie load 23 tonnes, GCW 70 tonnes

Packages

- **DRIVEFE** Driver convenience package FE
- **VISIFE** Visibility package FE
- **AIRFLOW** Airflow package with roof and side air deflectors and chassis fairings
- **AUDIODAB** Audio system with DAB radio and DAB amplifier
- **AUDIOPD** Preparation kit for DAB radio, including DAB amplifier

Chassis

- **FST-PAR** Two-leaf front parabolic springs (normal stiffness)
- **FAL7.1** Front axle load 7.1 tonnes
- **FAL7.5** Front axle load 7.5 tonnes
- **FAL8.0** Front axle load 8.0 tonnes
- **FAL9.0** Front axle load 9.0 tonnes
- **RAL21** Rear axles load 21 tonnes
- **RSTAB1** Rear anti-roll bar, normal stiffness
- **EBS-MED** EBS (Electronic Braking System), Medium package
- **EBS-STD** EBS (Electronic Braking System), Standard package
- **RST-PAR1** Rear parabolic leaf springs
- **ABS**
- **FRAME300** Frame rail section external height 300 mm
- **FST8080** Frame thickness - web 8.0 mm / flange 8.0 mm
- **FIL-FBEB** Frame inner liner from front of bogie to end of bogie
- **FIL-FBEF** Frame inner liner from front of bogie to end of frame
- **FIL-TXEB** Frame inner liner from transmission cross member to end of bogie
- **FIL-TXEF** Frame inner liner from transmission cross member to end of frame
- **2BATT170** Batteries, 2x170 Ah
- **2BATT225** Batteries, 2x225 Ah
- **ADR2** ADR adaptation, 1 switch in dashboard, 1 outside on back of cab
- **R160A56** Right 160-litre, D-shaped aluminium fuel tank, 560 mm high
Min volume 160l

■ Standard Equipment

□ Optional Equipment

For more detailed information about cab and powertrain equipment, please refer to separate specification sheets.

For all possible options and combinations of options please consult your Volvo sales contact who can create a specification to match your requirements using the Volvo Sales Support system (VSS).

The factory reserves the right to modify design and change equipment without previous notification.
The specification can vary from country to country.

- Max volume 630l
- **UL-FUEL** Without left side fuel tank
- **ADTP-R** AdBlue tank on right hand side
- **WHC-FIX1** One non-collapsible wheel chock
- **WHC-FIX2** Two non-collapsible wheel chocks
- **TB-L33** Tool box on left-hand side, 58-litre - width 330 mm, height 310 mm, depth 660 mm
- **TB-L75** Tool box on left-hand side, 106-litre - width 755 mm, height 430 mm, depth 550 mm
- **TOWMBRH** Towing member, high-mounted in centre of frame
- **RFEC-S** Straight-cut rear frame end
- **C-RI4040** Coupling Ringfeder 4040A G-150
- **C-RI5055** Coupling Ringfeder 5055A G-150
- **C-RO400G** Coupling Rockinger 400 G-150
- **C-RO430G** Towing coupling Rockinger 430 G-150
- **C-RO50** Coupling Rockinger 50 mm
- **TOWR-ONE** Rear towing device in frame-end cross member
- **TBC-EC** Trailer brake connection, European Community
- **TRBR-STA** Stationary trailer brake check
- **RUP-FIX2**
- **RFEND-B** Rear 3-piece mudguards (anti-spray) on all rear axles
- **RFEND-T** Transport mudguard
- **RFH-BAS** Basic mudguard installation height
- **RFH-HIG** High mudguard installation height
- **RFH-LOW** Low mudguard installation height
- **ATANK-AL** Aluminium air tanks
- **ATANK-ST** Steel air tanks
- **FRACLOS** Frame end closing

Rims and tyres

- **RT-AL** Brushed aluminium rims with standard holes (long stud fixing) on all axles
- **RT-ALDP** Dura-Bright® polished aluminium rims with standard holes (long stud fixing) on all axles
- **RT-STEEL** Steel rims on all axles
- **SPWT-F** Spare front wheel
- **SWCP-R** Spare wheel carrier mounted behind rear axle
- **SWCP-T** Spare wheel transport-mounted on top of frame
- **SWCP-TP** Spare wheel and carrier transport-mounted on top of frame

Powertrain equipment

- **TP-BAS**
- **TP-DICON**
- **TP-FUEC** Gear-changing software for regional haul
- **APF-ENH** I-Shift with enhanced PTO functions (Auto neutral for p. brake/Reverse inhibit/Split box connection)
- **APF-ENH2** I-Shift with enhanced PTO functions (Auto neutral for service brake/Split box connection)
- **CS39A-O** Single-plate clutch, plate diameter 395 mm
- **CS43B-O** Single-plate clutch, plate diameter 430 mm
- **TC-HWO** Oil cooler for hydraulic transmissions – water/oil
- **TC-MWO** Basic performance cooler for manual/I-Shift gearboxes - water/oil
- **AIRIN-HI** High air inlet
- **ACL1ST-S** Air cleaner with extra filter element
- **CCV-C** Closed crankcase ventilation
- **CCV-OX** Open extended crankcase ventilation with oil separator and maintenance-free gas centrifuge
- **AF-E** Electrically heated fuel filter
- **EST-AID** Engine intake air heater

MODEL RANGE

FE 64 Rigid Rear Leaf B-ride FE 64 R B

- **220EBH08** Engine block heater, 220 V, 0.8 kW
- **PTER-100** Rear engine, clutch-independent PTO, flange connection, DIN 100/ISO 7646
- **PTER-DIN** Rear engine, clutch-ind. PTO, splined shaft groove (fem), close-coupled pump DIN 5462/ISO7653
- **PTER1400** Rear engine, clutch-independent PTO, flange connection, SAE 1410/ISO 7647
- **PR-HP4T** Rear gearbox (top of converter) PTO with connection DIN 5462/ISO 7653 for pump, 400 Nm
- **PR-HP4TL** Rear gearbox (top of converter) low-speed PTO with connection DIN 5462/ISO 7653 for pump, 400 Nm
- **PR-HP6TH** Rear gearbox (top of converter) high-speed PTO with connection DIN 5462/ISO 7653 for pump, 600 Nm
- **PR-HP6TL** Rear gearbox (top of converter) low-speed PTO, connection DIN 5462/ISO 7653 for pump, 600 Nm
- **PTR-FH1** Rear gearbox PTO with flange connection DIN 90/ISO 7646 for propshaft 800 Nm
- **PTR-FH2** Rear gearbox PTO with flange connection DIN 90/ISO 7646 for propshaft, 430 Nm
- **PTR-FH5** Rear gearbox PTO with flange connection DIN 90/ISO 7646 for propshaft, 450 Nm
- **PTR-PH1** Rear gearbox PTO Hydrocar S81, connection DIN 5462/ISO 7653 for pump, 800 Nm
- **PTR-PH2** Rear gearbox PTO Hydrocar S84, connection DIN 5462/ISO 7653 for pump, 430 Nm
- **PTR-PH4** Rear gearbox PTO Hydrocar S88, connection DIN 5462/ISO 7653 for pump, 450 Nm
- **PTR-PK** Preparation kit for rear gearbox PTO
- **PTR-ZF2** Rear gearbox PTO ZF, flange connection DIN 100/ISO 7646 for propshaft, 410 Nm
- **PTRD-D1D** Rear gearbox dual PTO flange/propshaft DIN120/ISO7646, 550 Nm, pump DIN5462/ISO7647, 1000 Nm
- **PTRA-PH1** Extra rear gearbox PTO with dual S81 connections DIN 5462/ISO 7653 for pump
- **PTRA-PH2** Extra rear gearbox PTO with dual S84 connections DIN 5462/ISO 7653 for pump
- **HPG-F101** Gearbox-mounted hydraulic pump F1-101, fixed displacement, single flow
- **HPG-F41** Gearbox-mounted hydraulic pump F1-41, fixed displacement, single flow
- **HPG-F51** Gearbox-mounted hydraulic pump F1-51, fixed displacement, single flow
- **HPG-F61** Gearbox-mounted hydraulic pump F1-61, fixed displacement, single flow
- **HPG-F81** Gearbox-mounted hydraulic pump F1-81, fixed displacement, single flow
- **ETC** PTO speed control 900-1500 rpm with dash-mounted switch

Cab interior

- **STWPOS-L** Left-hand drive
- **STWPOS-R** Right-hand drive
- **TAS-DIG4** Gen 4 one-day digital tachograph, EC approved (GNSS & DSRC, EU 2020/1054)
- **IMMOBIL** Immobiliser
- **WARNLAMP** Portable amber and white warning lamp with batteries
- **TSRS** Road sign recognition
- **TSRS2** Road sign recognition (not ISA compliant)
- **WARNVEST** Reflective vest, fulfils European standard EN 471 class 2
- **AIDKIT** First aid kit containing sticking plaster, washing and drying pads, compresses, elastic bandages, respiratory mask, gloves and scissors.
- **AIDKIT1B** First aid kit fulfilling German requirements containing instruction, scissors, triangular cotton bandages, gauze bandages, bandaging cloths, gauze dressings, adhesive bandage, protective gloves, adhesive tape, first aid packets, rescue sheet.
- **CRUIS-E2** Cruise control with I-Roll
- **CRUISEC**

■ Standard Equipment

□ Optional Equipment

For more detailed information about cab and powertrain equipment, please refer to separate specification sheets.

For all possible options and combinations of options please consult your Volvo sales contact who can create a specification to match your requirements using the Volvo Sales Support system (VSS).

The factory reserves the right to modify design and change equipment without previous notification. The specification can vary from country to country.

Cab exterior

- **AUXFS** Extra footstep in cab side
- **CF-AFS** Retractable extra footstep in cab front bumper
- **RCABS-A** Air rear cab suspension
- **RCABS-M** Mechanical rear cab suspension
- **AD-ROOFA** Adjustable roof air deflector
- **AD-SIDES** Cab side air deflectors, short
- **HL-CLEAN** High-pressure headlamp cleaner
- **HL-ADJ** Manually adjustable headlamp beam
- **DRL-LED** Daytime running lamps (LED)
- **BEACON-P** Preparation kit for roof beacons
- **BEACONA2** Two amber LED beacons on cab front roof
- **HORN-F1S** Single-tone Jericho horn behind grille, operated by steering wheel buttons
- **HORN-R2S** Two chromed single-tone air horns on the roof, operated by steering wheel buttons

Superstructure preparations

- **FBA-BTF** Front body attachment brackets, lower, for flexible body
- **FBA-BTSF** Front body attachment brackets, lower, for semi-flexible body
- **RBA-T1** Rear body attachment plates
- **RBA-T2** Rear body attachment brackets, lower
- **HBA-FSFB** Holes for body attachments, flexible/semi-flexible body
- **TAILPREP** Tail lift preparation kit

Services

- **WVTA** Whole Vehicle Type Approved

MODEL RANGE

FE 64 Rigid Rear Leaf B-ride FE 64 R B
